

PRODUCT DATASHEET

Fila Night +



Area of application

- -Living areas
- -Bars and restaurants
- -Office
- -Outdoor balcony

Product benefit

- The 1.5mm thin filament boasts flexibility and thermal endurance
- Excellent light quality and 360-degree uniform illumination without shadows
- Playability and interactivity of flexible magnetic filaments

Product feature

- Integrated rechargeable lithium battery which can be charged USB cable



TECHNICAL DATA

Electrical data


Nominal wattage	1.2 W
Nominal voltage	5.0 V
Mains frequency	0 Hz
Nominal current	1000 mA
Protection class	III
Operating mode	Battery

Photometrical data


Luminous flux	100 lm
Luminous efficacy	MAX 80 lm/W
Color temperature	2700 K
Light color (designation)	Soft White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdc _m
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0





Dimensions & Weight

Length	131.5mm(5.2")
Width	131.5mm(5.2")
Height	321.0mm[389.0mm with Silicone rope](12.6"[15.3"])
Product weight	875.0g



unit: mm/Inch



-  Touch 1 time: 10% brightness
-  Touch 2 times: 100% brightness
-  Touch 3 times: Breathing
-  Touch 4 times: power off

Materials & Colors

Product color	Smoky / White
Housing color	Clear
Body material	PC Silica

Application & Mounting

Ambient temperature range	-20 °C...+40 °C
Type of connection	USB
Type of protection	IP20
Function	3-Step Touch Dim, 10%-100%-Breathing
Mounting type	Portable
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	15000H
---------------------------	--------

1) t_{th}: L70 / B50 @ 25 °C (Ta), t_{th}: L80 / B10 @ 25 °C (Ta), t_{th}: L90 / B10 @ 25 °C (Ta)

BATTERY

Type of Battery	Lithium ion
Battery size [GMS]	X103665 65mm*36mm*10mm
Number of included batteries	1
Nominal voltage of battery	3.7V
Nominal capacity of battery	3000mAh
Battery Charging time	4H
Usage time after fully charged	8H

Certificates & Standards

Standards	CE/FCC/RohS/REACH
Battery	UN38.3

EQUIPMENT / ACCESSORIES

- 1m usb-type c charging cable include

LOGISTICAL DATA

Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume (CBM)
Color box(1pcs/1box)	173 mm x 169 mm x 420mm(6.8"x6.7"x16.5")	1150g	0.012m ³
Shipping box(3pcs/1box)	362mm x 526 mm x 443 mm(14.3"x20.7"x17.4")	6373 g	0.084m ³

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.